

# 10Gb/100Gb Duplex Multimode 50/125 OM4 LSZH Fiber Patch Cable (LC/LC) - Aqua, 1M (3 ft.)

MODEL NUMBER: N820-01M-OM4



### **Highlights**

- Designed for 40/100-Gig Ethernet applications...OM4 Rated
- Backward compatible with existing 50/125 fiber
- Max 40/100Gb distance of 300 meters @850nm
- Low-Smoke, Zero Halogen (LSZH) Aqua jacket

#### **Package Includes**

 1 meter (3ft) Duplex Multimode 50/125 Aqua OM4 Fiber Patch Cable, LC/LC

#### **Features**

- 1 Meter ( 3ft ) LC/LC, OM4 Rated
- 40/100gb Ethernet speed to 300 meters @850nm
- Use with VCSEL and LED laser light sources
- High-Speed, High-Bandwidth, Low-Cost
- Backward compatible with legacy LAN's
- Ideal for Fibre Channel (SAN) applications
- IEEE 802.3ae and TIA LOMMF compliant

## **Specifications**

| OVERVIEW                |              |  |
|-------------------------|--------------|--|
| UPC Code                | 037332165213 |  |
| Technology              | Multimode    |  |
| Optical Mode            | OM4          |  |
| PHYSICAL                |              |  |
| FHISICAL                |              |  |
| Cable Jacket Color      | Aqua         |  |
| Connector Color         | Aqua         |  |
| Cable Jacket Material   | LSZH         |  |
| Cable Jacket Rating     | OFNR         |  |
| Clad Diameter (microns) | 125          |  |



| Core Diameter (microns)         | 50  |  |
|---------------------------------|---|--|
| Number of Fibers                | 2   |  |
| Cable Length (ft.)              | 3.3   |  |
| Cable Length (m)                | 1.01  |  |
| Cable Length (in.)              | 39.4  |  |
| Minimum Bend Radius             | 20 mm (Dynamic); 10 mm (Static)                       |  |
| Shipping Dimensions (hwd / in.) | 0.25 x 6.00 x 8.00                                    |  |
| Shipping Dimensions (hwd / cm)  | 0.64 x 15.24 x 20.32                                  |  |
| Shipping Weight (lbs.)          | 0.05  |  |
| Shipping Weight (kg)            | 0.02  |  |
| Fiber Cable Length              | 1M (3.3 ft)   |  |
|                                 |   |  |
| ENVIRONMENTAL                   |   |  |
| Operating Temperature Range     | -4° to 140°F (-20° to 60°C)                           |  |
| Storage Temperature Range       | -4° to 140°F (-20° to 60°C)                           |  |
| Operating Humidity Range        | 5% to 85% RH, Non-Condensing                          |  |
| Storage Humidity Range          | 35% to 65% RH, Non-Condensing                         |  |
| COMMUNICATIONS                  |   |  |
| Network Compatibility           | 1 Gbps (Gigabit); 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps |  |
| Attenuation @ 850NM             | 3.0 dB/km   |  |
| Insertion Loss                  | 0.20 dB   |  |
| CONNECTIONS                     |   |  |
| Side A - Connector 1            | LC DUPLEX (MALE)                                      |  |
| Side B - Connector 1            | LC DUPLEX (MALE)                                      |  |
| Endface Polish                  | PC  |  |
| FEATURES & SPECIFICATIONS       |   |  |
| Push/Pull Tabs                  | No  |  |
| Breakout                        | No  |  |
| Trunk                           | No  |  |
| STANDARDS & COMPLIANCE          |   |  |
| Product Compliance              | RoHS; REACH   |  |
| WARRANTY & SUPPORT              |   |  |



| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|-------------------------------------|---------------------------|
|-------------------------------------|---------------------------|



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.